

CORRESPONDENCE INSTRUCTIONS

All future correspondence and telephonic communications for this application should be directed to the following:

RICK D. NYDEGGER
WORKMAN, NYDEGGER & SEELEY
1000 Eagle Gate Tower
60 East South Temple
Salt Lake City, Utah 84111
Phone: (801) 533-9800
Fax: (801) 328-1707
EMAIL: RNYDEGGER@WNSPAT.COM

2009-07-10 10:00:00

UNITED STATES PATENT APPLICATION

of

Peter J. Potrebic

for

**SYSTEMS AND METHODS FOR
RECORDING FRAGMENTED PROGRAMS**

BACKGROUND OF THE INVENTION

1. The Field of the Invention

The present invention relates to systems and methods for recording fragmented programs. More specifically, the present invention is directed to systems and methods for identifying fragments of one or more programs that are related and are scheduled to be aired at discrete times, and for sequentially recording each of the fragments, without viewer intervention, so that a collection of the fragments is made available to the viewer.

2. The Prior State of the Art

Home entertainment systems are able to receive a variety of different channels from various sources at any time of the day or night. The channels carry public, cable or satellite television programming. When a program is aired at an inconvenient time, a viewer usually programs a videocassette recorder ("VCR"), a digital video recorder ("DVR"), or another recording system of the home entertainment system to record the program. Once recorded, the viewer can play the recorded version of the program at a more convenient time.

Frequently, programming received by a home entertainment system includes a program that is divided into a series of airings that are broadcast on non-regular or non-repeating intervals. Examples of such a program include mini-series, multi-day sporting events, and some sitcoms. If a viewer desires to record the series of airings of such mini-series, multi-day sporting events, or sitcoms, current methods include requiring the viewer to review the program schedule, identify the separate airings of the series, and separately program the recording system to record each airing of the program.

1 Alternative methods allow a viewer to program a recording system to record a
2 regularly repeating (i.e. every Tuesday from 8:00 p.m. to 8:30 p.m.) time slot. However,
3 current methods only record a program if the program is aired at the specified time slot.
4 As such, current recording systems do not always record the desired programming.
5 Furthermore, while current recording systems can be programmed to automatically record
6 programming aired at regularly repeating time slots, conventional systems have not been
7 capable of recording groups of related programs, which can also be designated
8 "fragmented programs." The inability of conventional systems to automatically record, for
9 example, all games in the World Series, or all episodes of a mini-series, has frequently
10 resulted in viewers having to personally identify each airing of the series while
11 programming their systems or to simply not be able to record the series of programs.

SUMMARY OF THE INVENTION

The present invention relates to systems and methods for recording fragmented programs. More specifically, the present invention is directed to systems and methods for identifying fragments of one or more programs that are related and are scheduled to be aired at discrete times, and for sequentially recording each of the fragments, without viewer intervention, so that a collection of the fragments is made available to the viewer. In this manner, the viewer is required simply to identify the fragmented program (e.g. an irregularly scheduled series), without having to personally identify the date and time of each airing.

Implementation of the present invention includes recording specific airings of programs in ways other than simply recording the same channel at the same time of day in an ongoing, regularly repeating manner. Thus, information from an electronic program guide is utilized to identify when each fragment of a fragmented program will air and to determine the relationship between programs.

A fragmented program is a program that has multiple airings broadcast over multiple days. Each airing is generally referred to as a fragment. Examples of a fragmented program include a mini-series, an ongoing sporting event, etc. A mini-series has a series of airings or fragments that are broadcast on consecutive days. Similarly, an ongoing sporting event is a multi-day event, such as the Olympics, the World Series, The Masters, or some other multi-day tournament that is broadcast over a series of days and the fragments may be broadcast on different networks. An ongoing television program includes a series of episodes that are aired on a regular basis. For purposes of this invention, ongoing television programs are of interest particularly when only some, but not all, of the individual airings are to be recorded.

1 Each fragment of a fragmented program is identified through the use of information
2 from an electronic program guide and the recording system is automatically programmed
3 to record each fragment as it airs. For example, a unique identifier assigned to a
4 fragmented program can be used to identify each of the fragments of the program. As
5 such, a television network may designate a group of different sitcoms (e.g. a set broadcast
6 during a single evening) as being related for purposes of recording, causing the group of
7 sitcoms to be collectively designated as a fragmented program so as to be automatically
8 recorded without requiring the viewer to select each sitcom included in the group.

9 Depending on the nature of the programs and user preferences, each fragment of a
10 fragmented program can be recorded in proper order to provide the viewer with a complete
11 version of the fragmented program in the order that it originally aired. Alternatively, the
12 recording system can automatically differentiate between first-run and re-run episodes of
13 an ongoing television program (e.g. a sitcom) and record each new episode of the program
14 throughout a television season, while automatically refraining from recording re-runs of
15 episodes already recorded, thereby providing a viewer with a collection of all of the new
16 episodes of the program at the end of the season. This represents an example of how
17 ongoing programs can be recorded in ways other than simply recording the same channel
18 at the same time of day in a regularly repeating manner.

19 Implementation of the invention to utilize information from an electronic program
20 guide to identify when each fragment of a fragmented program will air and to determine
21 the relationship between programs eliminates the need of a viewer to personally identify
22 the date and time of the airing of each fragment. Instead, the viewer simply identifies the
23 fragmented program that he/she desires the system to record, and then the system
24 automatically identifies when and on which channel each of the fragments will air, and

1 automatically records each fragment as it airs. Furthermore, if a particular episode airs
2 more than once then the system has multiple opportunities to record the particular episode
3 of the fragmented program. As such, the recording of programs is optimized by avoiding
4 conflicts that occur when multiple programs that are to be recorded air at the same time.

5 Additional features and advantages of the invention will be set forth in the
6 description which follows, and in part will be obvious from the description, or may be
7 learned by the practice of the invention. The features and advantages of the invention may
8 be realized and obtained by means of the instruments and combinations particularly
9 pointed out in the appended claims. These and other features of the present invention will
10 become more fully apparent from the following description and appended claims, or may
11 be learned by the practice of the invention as set forth hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to describe the manner in which the above-recited and other advantages and features of the invention can be obtained, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

Figure 1 illustrates an exemplary system that provides a suitable operating environment for the present invention;

Figure 2 is a flowchart that illustrates an exemplary embodiment of the present invention that identifies a fragmented program and determines which fragments to record;

Figure 3 illustrates an exemplary recording list that is stored at a management system and lists the fragmented programs that are to be recorded;

Figure 4 illustrates a portion of an exemplary electronic programming guide that relates to Monday programming and may be used in association with a home entertainment system;

Figure 5 illustrates a portion of an exemplary electronic programming guide that relates to Tuesday programming and may be used in association with a home entertainment system;

Figure 6 illustrates a portion of an exemplary electronic programming guide that relates to Wednesday programming and may be used in association with an entertainment system;

1 Figure 7 illustrates a portion of an exemplary electronic programming guide that
2 relates to Thursday programming and may be used in association with an entertainment
3 system;

4 Figure 8 illustrates a portion of an exemplary electronic programming guide that
5 relates to Friday programming and may be used in association with an entertainment
6 system;

7 Figure 9 is a flowchart that illustrates an exemplary embodiment for removing a
8 program from a recording list once all fragments of the program have aired and for
9 reminding a viewer of the reoccurrence of a fragmented program; and

10 Figure 10 illustrates a recording list that removes fragmented programs once all
11 fragments have been aired, as identified in the exemplary embodiment of Figure 9.

DETAILED DESCRIPTION OF THE INVENTION

The present invention relates to systems and methods for recording fragmented programs. More specifically, the present invention is directed to systems and methods for identifying fragments of one or more programs that are related and are scheduled to be aired at discrete times, and for sequentially recording each of the fragments, without viewer intervention, so that a collection of the fragments is made available to the viewer.

Throughout the following disclosure, reference is made to the recording of one or more fragmented programs. In the disclosure and in the claims the term "fragmented program" refers to a program that is divided into a series of airings or a plurality of programs that are related in some way to each other or may be associated with each other. Furthermore, in the disclosure and in the claims the term "fragment" refers to one or more of the series of airings of a fragmented program. In one embodiment, a fragment refers to an episode, which corresponds to a fragmented program that is scheduled to air for an entire season, wherein at least two fragments of the series are temporally separated from each other, as will be further explained below. In another embodiment, a fragment refers to one of a plurality of broadcasts of a particular event.

The embodiments of the present invention may comprise a special purpose or general purpose computer including various computer hardware, as discussed in greater detail below. Set top boxes that enhance the capabilities of conventional televisions represent an example of a special purpose computer. The embodiments may further comprise multiple computers linked in a networked environment.

Embodiments within the scope of the present invention also include computer-readable media for carrying or having computer-executable instructions or data structures stored thereon. Such computer-readable media can be any available media that can be

1 accessed by a general purpose or special purpose computer. By way of example, and not
2 limitation, such computer-readable media can comprise physical storage media such as
3 RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or
4 other magnetic storage devices, or any other medium that can be used to carry or store
5 desired program code means in the form of computer-executable instructions or data
6 structures and that can be accessed by a general purpose or special purpose computer.
7 When information is transferred or provided over a network or another communications
8 connection (either hardwired, wireless, or a combination of hardwired or wireless) to a
9 computer, the computer properly views the connection as a computer-readable medium.
10 Thus, such a connection is also properly termed a computer-readable medium.
11 Combinations of the above should also be included within the scope of computer-readable
12 media. Computer-executable instructions comprise, for example, instructions and data
13 which cause a general purpose computer, special purpose computer, or special purpose
14 processing device to perform a certain function or group of functions.

15 The invention will be described in the general context of computer-executable
16 instructions, such as program modules, being executed by set-top boxes or other
17 computers. Generally, program modules include routines, programs, objects, components,
18 data structures, etc. that perform particular tasks or implement particular abstract data
19 types. Computer-executable instructions, associated data structures, and program modules
20 represent examples of the program code means for executing steps of the methods
21 disclosed herein. The particular sequence of such executable instructions or associated
22 data structures represents examples of corresponding acts for implementing the functions
23 described in such steps.
24

1 The following disclosure of the present invention is grouped into two subheadings,
2 namely "Exemplary Operating Environment" and "Recording Fragmented Programs." The
3 disclosure relating to the first subheading provides an example of a suitable environment
4 for implementation of the present invention, while the disclosure corresponding to the
5 second subheading provides examples of implementing the present invention. The
6 utilization of the subheadings is for convenience of the reader only and is not to be
7 construed as limiting in any sense.

8 9 Exemplary Operating Environment

10 Figure 1 and the corresponding discussion are intended to provide a general
11 description of a suitable environment in which the invention may be implemented. In the
12 discussion, reference is made to a home entertainment system that may be used for
13 displaying and/or recording programming. For purposes of this description and in the
14 claims, a "home entertainment system" may be a display unit, such as a television screen,
15 coupled to a processing device for performing the data processing steps disclosed herein,
16 or may include any number of interconnected consumer electronic devices, one of which
17 having a processing device for performing the data processing steps disclosed herein.
18 Examples of such consumer electronic devices include a video cassette recorder ("VCR"),
19 a video game system, a stereo system, a television or monitor with data processing
20 capabilities, a cable television box, a digital satellite system receiver ("DSS"), a digital
21 video broadcasting system ("DVB"), a digital versatile disc system ("DVD"), a set-top box
22 that serves as an Internet terminal, and any other device capable of processing data as
23 described herein. Furthermore, the term "home entertainment system" is to be understood
24 as a term that broadly describes a television-viewing environment, whether it is located in

1 a viewer's home, at a place of business, in the public, or at any other location. Also for
2 purposes of this description and in the claims, the term "programming" includes both the
3 viewable portions of moving image data and its associated sound data.

4 In one embodiment, the present invention is implemented in a system that uses a
5 conventional television screen or other display unit to display information and includes a
6 WebTV® set-top box or a similar Internet terminal that has been adapted to perform the
7 operations that include composing, sending and receiving email, browsing the World Wide
8 Web ("Web"), accessing other segments of the Internet, and otherwise displaying
9 information. An Internet terminal typically uses standard telephone lines, Integrated
10 Services Digital Network (ISDN) lines, cable lines associated with cable television service,
11 or the like to connect to the Internet or other wide area networks.

12 Figure 1 illustrates a home entertainment system 10 that includes a management
13 system 12, a display device 14 and an audio system 16. Management system 14 may be a
14 set-top box or Internet terminal that has been adapted to perform the operations disclosed
15 herein. Management system 12 may be integrally positioned with or separate from display
16 device 14, which may be a high definition television display, a standard television display,
17 a flat panel display, a projection device, a high definition television display, a computer
18 monitor, or any other device capable of displaying viewable video image data. Audio
19 system 16 may be a speaker, a stereo system, or any device capable of emitting sound data,
20 and similarly may be integrally positioned with or separate from display device 14.

21 Management system 12 includes a signal input 18, which receives programming
22 from a signal source 20. The programming is transmitted from signal source 20 to signal
23 input 18 via a programming input line 22, which can be a cable or optic connection, a
24

1 terrestrial antenna system, a satellite system, or any device or system capable of
2 transmitting programming to home management system 12.

3 The signal source 20 may be either a single channel signal source or a multiple
4 channel signal source. A single channel signal source provides programming from a
5 recorded medium, such as a videocassette, compact disc, etc. Examples of a single channel
6 signal source include a VCR, a DVD, and the like. Alternatively, a multiple channel signal
7 source includes any system or device that is capable of sending a signal that may be
8 received by a satellite receiver, a cable or optic connection, a terrestrial antenna, or the
9 like. Examples of a multiple channel signal source include DSS/DVB, a cable box, locally
10 broadcast programming (i.e. programming broadcast using UHF or VHF), and the like.

11 While Figure 1 illustrates home entertainment system 10 as having a single
12 programming input line 22 and a single signal source 20, there can instead be a plurality of
13 programming input lines that transmit programming from a plurality of signal sources. In
14 such embodiments, the home entertainment system may receive the programming from
15 one signal source or from a plurality of signal sources at a time.

16 Management system 12 also includes a user input interface 24, which receives
17 input from an input device 26, such as a remote control, keyboard, microphone, or any
18 other device capable of generating electronic instructions for management system 12.
19 Input device 26 is communicatively coupled to management system 12 over an input link
20 28 so as to enable such control. Input device 26 generates electronic instructions over
21 input link 28 in response to preprogrammed data or in response to a viewer pressing
22 buttons on input device 26. Input device 26 may also control Web browser software
23 within management system 12 as when management system 12 is a set-top box or an
24 Internet terminal that has been adapted to perform the operations disclosed herein. For

1 instance, input device 26 may be programmed to turn on home entertainment system 10
2 and to tune management system 12 to a channel.

3 Figure 1 illustrates a signal recorder 30, which is capable of receiving video and/or
4 audio data and recording the data on a storage medium. Video signals are transmitted to
5 signal recorder 30 and/or display device 14 by video image link 32, examples of which
6 include a radio-frequency ("RF") link, an S-video link, a composite link, or any other
7 equivalent form of video image link. Similarly, audio link 34 transmits audio data from
8 management system 12 to audio system 16 or to signal recorder 30.

9 The operation of management system 12 is controlled by a central processing unit
10 ("CPU"), illustrated as processing unit 36, which is coupled to an application-specific
11 integrated circuit ("ASIC") 38 and uses computer-executable instructions implemented in
12 software and/or hardwired logic circuitry. Processing unit 36 and ASIC 38 are coupled via
13 a system bus 40, which also interconnects various other system components, such as the
14 system memory 42, mass storage interface 44, user interface 24 and signal input 18.
15 Processing unit 36 executes software designed to implement features of management
16 system 12 including features of the present invention. ASIC 38 contains circuitry that is
17 used to implement certain functions of management system 12. Instructions, data, and
18 other software necessary for the operation of processing unit 36 and ASIC 38 may be
19 stored in the system memory 42, such as in read-only memory ("ROM") 46 and/or in
20 random-access memory ("RAM") 48, and/or in a mass storage device 50, which is coupled
21 to mass storage interface 44. ROM 46, RAM 48 and mass storage device 50 are
22 communicatively coupled to ASIC 38 so as to be readable by ASIC 38 and so that data
23 may be written from ASIC 38 to RAM 48 and possibly mass storage device 50.
24

1 Mass storage device 50 may be a magnetic hard disk 52 or any other magnetic or
2 optical mass memory device that is capable of storing large amounts of data. Any desired
3 computer-readable instructions or data, including application programs 54, other program
4 modules 56, and an electronic programming guide ("EPG") 58, which specifies the
5 broadcast times and channels of programs can be stored in mass storage device 50. Mass
6 storage device 50 can also be used to record video data 53, in which case, management
7 system 12 generates as a digital video recorder.

8 EPG data may be obtained in a variety of manners. For instance, the EPG data can
9 be supplied to management system 12 by a remote computer 60, such as a server, and
10 stored on mass storage device 50. The EPG data is supplied on a regular basis to
11 continually maintain a current schedule of programming at the management system 12.
12 Where home entertainment system 12 is associated with the Internet, the data included in
13 the EPG may be downloaded from the Internet. Alternatively, the EPG may delivered to
14 the home entertainment system by using a direct-dial communication over standard
15 telephone lines, or by using data transmission over the cable television infrastructure, a
16 satellite network, an over-the-air broadcasting or any other available medium.

17 In the embodiment where management system 12 is associated with the Internet,
18 management system 12 communicates with a remote computer 60 via a wide area network
19 ("WAN") 62 by including a serial port interface 64 that is interposed between the system
20 bus 40 and a modem 66, a wireless link, or other means for establishing communications
21 over a WAN that may be internal or external to management system 12. Management
22 device 12 is also capable of transmitting information via the Internet by direct-dial
23 communication over standard telephone lines, or by using any other available
24 communication medium.

1 While serial port interface 64 may be utilized to connect a modem 66 for
2 communicating across a WAN, serial port interface may also be utilized to connect other
3 consumer electronic devices, such as video game 68, and/or various input devices, such as
4 a keyboard (not shown) or joystick (not shown), to management device 12.

5 Referring now to signal input 18, if the signal on programming input line 22
6 includes multiple channels, a tuner 70 included in signal input 18 tunes to a selected
7 channel in the signal. Multiple tuners 70 can be used to provide enhanced viewing
8 features, such as picture, recording one channel while viewing another, and recording a
9 plurality of channels simultaneously. A signal decoder 72 converts video data from an
10 analog format to a digital format, or from a digital format to an analog format, in the event
11 that ASIC 38 and tuner 70 employ different formats. Video decoder 72 also decodes video
12 data from a compressed video format (e.g. MPEG). In embodiments where the
13 management system 12 includes multiple tuners 70, management system 12 may also
14 include multiple signal decoders 72 to perform the operations disclosed herein.

15 Management system 12 also includes a video output 74, which may include a video
16 encoder and/or a video converter. The video encoder assigns a code to frames of video
17 data that are transmitted across a video image link 32 and switches between analog and
18 digital formats as necessary. Similarly, audio output 76 can include an audio converter to
19 provide the necessary switching between analog and digital formats.

20 While Figure 1 and the corresponding discussion above provide a general
21 description of a suitable environment in which the invention may be implemented, it will
22 be appreciated that the features of the present invention disclosed herein may be practiced
23 in association with a variety of different system configurations.

Recording Fragmented Programs

As provided above, the present invention relates to systems and methods for recording fragmented programs. More specifically, the present invention is directed to systems and methods for identifying fragments of one or more programs that are related and are scheduled to be aired at discrete times, and for sequentially recording each of the fragments, without viewer intervention, so that a collection of the fragments is made available to the viewer.

With reference to Figure 2, an embodiment of the present invention is illustrated in which a fragmented program is identified and a determination is made as to which fragments to record. A fragmented program may be directly identified by a viewer or may be identified upon selecting a fragmented program from a listing of categories. Once identified, the desired fragments of the program are recorded, as will be further explained below.

In the embodiment illustrated in Figure 2, execution begins at decision block 80 for a determination as to whether or not a fragmented program is selected from a category list, which is a listing of various types of fragmented programs. Examples of categories of fragmented programs include sporting events, mini-series, sitcoms, news broadcasts, and the like. The category list is displayed on a display device of a home entertainment system, such as display device 14 of Figure 1. A user may provide input to select a category and then to select a fragmented program under the selected category, or may directly identify a fragmented program to record.

Therefore, if at decision block 80 it is determined that a category list will be used to select a fragmented program, execution proceeds to step 82 for the display of the various categories. As provided above, examples of categories of fragmented programs include

1 sporting events, mini-series, sitcoms, news broadcasts, and the like. A menu system is
2 used to display the categories on a display device and to interface with the viewer. A
3 viewer may select a category by providing input through the use of an input device, such as
4 input device 26 in Figure 1.

5 At decision block 84 a determination is made as to whether or not a viewer has
6 selected one of the displayed categories. If a viewer has not selected a displayed category,
7 execution returns back to step 82 until a displayed category is selected.

8 Once a category is selected, execution proceeds to step 86 for the identification of
9 the fragmented programs that can be grouped under the selected category and will be aired
10 on a channel during a specific period of time. The recording system uses electronic
11 program guide data that provides information to identify the airings of the fragmented
12 programs to record. For instance, the title of a program (e.g. "Olympics") can be used to
13 determine that fragments are related one to another. In other instances, conventional
14 electronic program guide information is enhanced or supplemented by information that
15 specifies that programs are related. One example of this technique is a television network
16 designating a group of sitcoms as being related for purposes of recording. Therefore, the
17 group of sitcoms can be automatically recorded without requiring the viewer to
18 individually select each sitcom included in the group.

19 In one embodiment, EPG data is enhanced by including a unique identifier that is
20 specific to a fragmented program and is common to each fragment within the particular
21 fragmented program to facilitate the identification of fragmented programs. In another
22 embodiment, EPG data, such as the title of each program, is utilized to identify the
23 fragmented programs. Once identified, step 88 displays on the display device the title of
24

1 each fragmented program that is scheduled to air during the specific period of time to
2 allow the viewer to select one or more of the programs to record.

3 Therefore, by way of example, if the category selected by the viewer is entitled
4 "mini-series," the system searches EPG data to identify all mini-series that are scheduled to
5 air on any channel received by the home entertainment system during a specific period of
6 time. Once identified, the title of each mini-series that will air during the specific period of
7 time is displayed on the display device to allow a viewer to determiner whether or not to
8 record any of the displayed fragmented programs.

9 Once the fragmented programs of the selected category have been displayed,
10 execution proceeds to decision block 90 for a determination as to whether or not a viewer
11 has selected one of the displayed fragmented programs for recording. If a viewer has not
12 selected one of the displayed fragmented programs, execution returns back to step 88 to
13 wait for viewer input. Once a viewer has selected one of the displayed fragmented
14 programs, execution proceeds to step 94 for the identification of each of the various
15 fragments of the fragmented program, as will be further explained below.

16 Returning back to decision block 80, if it is determined that a category list will not
17 be used to select a fragmented program, execution proceeds to step 92 to receive viewer
18 input regarding the fragmented program that the viewer desires to have recorded. As
19 provided above, a viewer may directly select a fragmented program to record by inputting
20 information to the home entertainment system, such as the title of the program or by
21 selecting a single fragment included in the fragmented program from a user interface
22 associated with an electronic program guide.

23 Once a fragmented program has been selected by a viewer to be recorded,
24 execution proceeds to step 94 for an identification of each of the various fragments of the

1 fragmented program. A program may be fragmented in a variety of ways. For example,
2 the program may be a mini-series that is aired at a specific time during consecutive days of
3 a week. Alternatively, a fragmented program may be a sporting event that takes place over
4 a plurality of days, such as the Major League Baseball World Series ("World Series"), the
5 National Basketball Association ("NBA") Finals, a golf tournament, the Summer or Winter
6 Olympics, etc. At times the sporting event is aired on consecutive days, such as in the case
7 of a golf tournament or the Olympics. However, other sporting events are aired on non-
8 consecutive days, such as in the case of the World Series or NBA Finals. A fragmented
9 program may also include a series of programs that are related and are broadcast on a given
10 network for a specific period of time, such as "James Bond Week" that airs various James
11 Bond movies during a week on a given network. Other examples of fragmented programs
12 are programs that include regularly aired episodes or a plurality of programs that are
13 designated as being related by having similar actors or themes. In view of the foregoing, it
14 is to be understood that other types of fragmented programs exist, and the general
15 principles disclosed herein can be used to record the fragments of such fragmented
16 programs.

17 Therefore, at step 94 the system utilizes EPG data to identify each of the fragments
18 that correspond to the selected fragmented program. Each fragment may be identified by a
19 unique identifier assigned to the fragmented program coupled with a unique identifier for
20 each fragment. Alternatively, title information may be used to identify the various
21 fragments of the program.

22 Once all of the fragments of the selected program are identified, execution proceeds
23 to decision block 96 for a determination as to whether or not the fragments are episodes.
24 As mentioned above, one example of a fragmented program includes a television program

1 (i.e. sitcom) that includes a series of episodes. As used herein, the term "episode" refers to
2 a fragment of an ongoing, regularly repeating program. In an embodiment of the present
3 invention, a television program that includes episodes is treated differently than other types
4 of fragmented programs because the episodes may be re-runs that are undesirable for
5 recording. In another embodiment, a viewer may want to record the re-runs, such as when
6 the viewer desires a non-redundant copy of all of the episodes of a particular program,
7 whether the episodes are first-run episodes or re-run episodes.

8 Therefore, in accordance with the illustrated embodiment, if a determination is
9 made at decision block 96 that the fragments are not episodes, then execution proceeds to
10 step 98, where the system automatically determines the start time for each fragment. The
11 start time includes the channel, date and time the fragment is scheduled to air and is
12 obtained from EPG data. The system is then automatically programmed at step 100 to
13 record each of the fragments of the program.

14 Returning back to decision block 96, if it is determined that the fragments are
15 episodes, then execution proceeds to step 102 where an episode is identified. Decision
16 block 104 then determines whether the episode is a re-run. For purposes of this document,
17 a "re-run" is an episode of a fragmented program that has already been broadcast at least
18 once before. Furthermore, for purposes of this document a re-run may be a fragment of a
19 fragmented program that has already been recorded. If the identified episode is not a re-
20 run, the system is automatically programmed for the recording of the identified episode at
21 step 106.

22 Once the system is automatically programmed to record the identified episode,
23 execution proceeds to decision block 110 for a determination as to whether or not another
24 episode of the fragmented program exists. If it is determined that another episode does not

1 exist, execution returns back to start. However, if another episode exists, execution returns
2 to step 102 for the identification of another episode at step 102 and for a determination at
3 step 104 as to whether or not the identified episode is a re-run.

4 With reference to decision block 104, if it is determined that an identified episode
5 is a re-run, execution proceeds to decision block 108 for a determination as to whether or
6 not to record re-runs. A viewer may opt to have the system automatically record all of the
7 episodes or to only record new episodes of the fragmented program. When the system
8 records only new episodes, the system records each first-run episode of a particular
9 fragmented program while automatically refraining from recording re-runs of episodes
10 already recorded. Therefore, if a viewer does not desire to have the system record re-runs,
11 execution proceeds to decision block 110 for a determination as to whether or not another
12 episode exists. As above, if another episode does not exist, execution returns back to start.
13 Alternatively, if another episode exists, execution returns back to step 102 for the
14 identification of another episode.

15 Alternatively, if at decision block 108 it is determined that the user desires to have
16 the system automatically record all of the episodes, including re-runs, then execution
17 proceeds to step 106 where the system is automatically programmed for the recording of
18 the identified episode. Execution then proceeds to decision block 110 for a determination
19 as to whether or not there is another episode. If another episode does not exist, execution
20 returns back to start. If another episode does exist, execution proceeds to step 102 for the
21 identification of a subsequent episode. This process is continued until all of the episodes
22 of the fragmented program have been identified and a determination is made as to which
23 episodes of the fragmented program to automatically record. Of course, the process of
24 identifying all fragments of the fragmented program may extend through a period of

1 several days to as long as an entire television season, as the electronic program guide data
2 is repeatedly updated.

3 Once the system has been automatically programmed in steps 100 and 106 to
4 record all of the desired fragments of the program, each fragment is recorded as it airs.
5 The EPG data informs the system as to any changes in the programming, such as when a
6 fragment is preempted by another program, when one or more of the fragments are no
7 longer scheduled to air, or when a fragment has been moved from one channel to another
8 channel.

9 Figures 3 – 8 and the corresponding disclosure provide an example for recording
10 various types of fragmented programs in accordance with the exemplary embodiment of
11 Figure 2. The types of fragmented programs identified in Figures 3 – 8 include a mini-
12 series, an ongoing sporting event, and a television program having a series of episodes.

13 As indicated above, a viewer may select one or more fragmented programs to be
14 automatically recording either by using a categories list or by directly providing the title of
15 each program. Once one or more fragmented programs have been selected, the
16 information is stored at the home entertainment system, such as on a mass storage device
17 of a management system (i.e. management system 12 of Figure 1).

18 Referring now to Figure 3, a recording list is illustrated as recording list 120, which
19 provides a list of fragmented programs that have been selected by a viewer for the system
20 to automatically record. The fragmented programs included in the recording list 120 are a
21 mini-series 122 entitled “Lonesome Dove”, a sporting event 124 entitled “World Series”,
22 and a television program 126 entitled “Friends.”

23 Figures 4 – 8 provide exemplary portions of an EPG for five consecutive days,
24 namely Monday through Friday, and are respectively labeled as EPG portions 130, 140,

FILED 02 FEB 2006

1 150, 160, and 170. Each EPG portion includes the scheduled start time for the
2 programming listed, such as start times 132 of Figure 4, and the channel on which the
3 programming is scheduled to air, such as channels 134 of Figure 4.

4 With reference to the fragmented program mini-series 122 of Figure 3, a first
5 fragment of mini-series 122 is scheduled to be aired on Monday from 5:30 – 7:30 (as
6 indicated by mini-series fragment 138 of Figure 4), a second fragment is scheduled to be
7 aired on Tuesday from 5:30 – 7:30 (as indicated by mini-series fragment 148 of Figure 5),
8 a third fragment is scheduled to be aired on Wednesday from 5:30 – 7:30 (as indicated by
9 mini-series fragment 158 of Figure 6), and a fourth fragment is scheduled to be aired on
10 Thursday from 5:30 – 7:30 (as indicated by mini-series fragment 168 of Figure 7). After
11 7:30 on Thursday, the mini-series 122 is over since all of the fragments have aired.

12 Therefore, in accordance with the embodiment illustrated in Figure 2, once mini-
13 series 122 has been selected by a viewer and is on the recording list, as illustrated in
14 Figure 3, each of the fragments of mini-series 122 is identified. The fragments of mini-
15 series 122 are then determined to not be episodes since mini-series 122 is only aired during
16 a four-day period rather than over an entire season or a substantial portion of the season.
17 The start time, including the date and channel, is then automatically determined from the
18 EPG data. The start times for the fragments of mini-series 122 are Monday from 5:30 –
19 7:30, Tuesday from 5:30 – 7:30, Wednesday from 5:30 – 7:30, and Thursday from 5:30 –
20 7:30, which each fragment being aired on channel 28, as respectively illustrated in
21 Figures 4 – 7. The system is then automatically programmed to record each of the
22 fragments of mini-series 122 as each fragment airs.

23 With reference to the fragmented program sporting event 124 of Figure 3, a first
24 fragment of sporting event 124 is illustrated as sporting event fragment 136 in Figure 4,

1 which is scheduled to be aired on Monday from 5:00 – 7:30, a second fragment is
2 illustrated as sporting event fragment 156 of Figure 6, which is scheduled to be aired on
3 Wednesday from 5:00 – 7:30, and a third fragment is illustrated as mini-series fragment
4 158 of Figure 6, which is scheduled to be aired on Friday from 5:00 – 7:30. Since the
5 MLB World Series is a best-of-seven tournament, other fragments of sporting event 124
6 would also be scheduled but are not illustrated. The total number of fragments can be from
7 four to seven fragments depending on the number of games that are won by each team.
8 Once a team has won four games of the World Series, sporting event 124 is over since all
9 of the fragments have aired.

10 Therefore, in accordance with the embodiment illustrated in Figure 2, once sporting
11 event 124 has been selected by a viewer and is on the recording list, as illustrated in
12 Figure 3, each of the fragments is identified using EPG data. The fragments of sporting
13 event 124 are then determined to not be episodes since sporting event 124 is only aired
14 until one team wins four games of the tournament. The start time, including the date and
15 channel, is then automatically determined from the EPG data and the system is
16 automatically programmed to record each of the fragments of mini-series 122 as each
17 fragment airs. As the EPG data is updated as to the number of fragments that will air for
18 sporting event 124, the EPG data then updates the recording system so as to know the
19 number of fragments to record.

20 With reference to the fragmented program television program 126 of Figure 3, a
21 first fragment of television program 126 is scheduled to be aired on Monday from 5:00 –
22 5:30 (as indicated by television program fragment 137 of Figure 4), a second fragment is
23 scheduled to be aired on Tuesday from 5:00 – 5:30 (as indicated by television program
24 fragment 148 of Figure 5), a third fragment is scheduled to be aired on Wednesday from

1 5:00 – 5:30 (as indicated by television program fragment 158 of Figure 6), and a fourth
2 fragment is scheduled to be aired on Wednesday from 7:00 – 7:30 (as indicated by
3 television program fragment 155 of Figure 6), a fifth fragment is scheduled to be aired on
4 Thursday from 5:00 – 5:30 (as indicated by television program fragment 167 of Figure 7),
5 and a sixth fragment is scheduled to be aired on Friday from 5:00 – 5:30 (as indicated by
6 television program fragment 177 of Figure 8).

7 Therefore, in accordance with the embodiment illustrated in Figure 2, once
8 television program 126 has been selected by a viewer and is on the recording list, as
9 illustrated in Figure 3, each of the fragments of television program 126 is then identified.
10 The fragments of television program 126 are determined to be episodes since fragments of
11 television program 126 will air over an entire television season or a substantial portion
12 thereof. Each episode is examined independently to differentiate first-run episodes from
13 re-run episodes. The episodes illustrated in Figures 4 – 8 that air on channel 28, namely
14 television program fragments 137, 147, 157, 167 and 177 are re-run episodes. However,
15 the television program fragment 155, which is scheduled to be aired on channel 26 is a new
16 episode.

17 Therefore, in accordance with the embodiment of Figure 2, if a viewer desires to
18 record only the new episodes of television program 126, the only illustrated fragment that
19 is recorded is television program fragment 155 of Figure 6 because it is the only fragment
20 that is a first-run episode. All other new episodes throughout the season are also recorded
21 by the system to provide a collection of all of the first-run episodes at the end of the
22 season.

23 In a further embodiment, if one or more of the actors of television program
24 fragment 155 of Figure 6 are also scheduled to appear on television program fragment 154

1 and similar themes are to be portrayed to cause fragments 154 and 155 to be related, the
2 system views fragments 154 and 155 as two fragments of the same fragmented program
3 and both fragments 154 and 155 are recorded by the system.

4 In the example illustrated in Figures 4 – 8, the management system utilized as part
5 of the recording system includes a plurality of tuners to allow for the recording of multiple
6 programs that are aired at concurrent times (i.e. mini-series fragment 138 and sporting
7 event fragment 136 of Figure 4). Alternative embodiments allow for a single tuner to be
8 used to record fragmented programs. In the event of a programming conflict where
9 multiple fragmented programs are scheduled to be aired at concurrent times and thus
10 cannot all be recorded with the use of a single tuner, the system may search the EPG data
11 to determine whether one of the fragments will be aired later as a re-run on the same or a
12 different channel to allow for all of the desired fragments to be recorded. Alternatively, a
13 priority system may be established so that when a programming conflict occurs, the tuner
14 is used to record the fragmented program with the highest priority.

15 With reference to Figure 9, a flowchart is illustrated to indicate what happens after
16 a fragment of a program is recorded. Once all of the fragments have been aired, the
17 fragmented program is removed from the recording list. However, if the fragmented
18 program is repetitive, such as the Summer Olympics that airs every four years, the program
19 is removed from the recording list and a reminder is set to remind the viewer prior to the
20 subsequent airing of the fragmented program that the fragmented program will air.

21 Therefore, in Figure 9, execution begins at decision block 180 where a
22 determination is made as to whether or not all the fragments have been aired of the
23 fragmented program. If all of the fragments have not been aired, execution returns back to
24 start to allow for the airing of all of the fragments. When all of the fragments have been

1 aired, execution proceeds to step 182 where the system removes the fragmented program
2 from the program list.

3 The removal of a fragmented program from a recording list is illustrated in Figure
4 10 by recording list 190, which is the state of recording list 120 of Figure 4 after all of the
5 fragments of mini-series 122 and sporting event 124 have been aired. In Figure 10, only
6 television program 126 remains on recording list 190.

7 Returning to Figure 9, once the fragmented program is removed from the program
8 list at step 182, a determination is made at decision block 184 as to whether or not the
9 fragmented program that has been removed from the recording list is a reoccurring
10 program. Examples of reoccurring fragmented programs include the MLB World Series,
11 which airs annually, the Summer Olympics, which airs every four years, a television
12 program that airs new episodes during each television season, etc.

13 Therefore, if the fragmented program that was removed from the recording list is
14 not reoccurring, execution returns back to start. However, if the fragmented program is
15 reoccurring, execution proceeds to step 186 for the identification of when the fragmented
16 program will reoccur, which may be performed through the use of EPG data. Execution
17 then proceeds to step 188 where the system automatically sets a reminder to be displayed
18 to determine at a future time as to whether or not the system is to automatically record the
19 reoccurrence of the fragmented program. For example, a reminder is set to inform the
20 viewer prior to the next occurrence of the World Series that the World Series will soon air
21 and inquires as to whether or not the viewer desires to record the various fragments of the
22 subsequent airings of the World Series.

23 Thus, as indicated above, the present invention is related to systems and methods
24 for identifying fragments of one or more programs that are related and are scheduled to be

1 aired at discrete times, and for sequentially recording each of the fragments, without
2 viewer intervention, so that a collection of the fragments is made available to the viewer.
3 The present invention may be embodied in other specific forms without departing from its
4 spirit or essential characteristics. The described embodiments are to be considered in all
5 respects only as illustrative and not restrictive. The scope of the invention is, therefore,
6 indicated by the appended claims rather than by the foregoing description. All changes
7 which come within the meaning and range of equivalency of the claims are to be embraced
8 within their scope.

9 What is claimed and desired to be secured by United States Letters Patent is:
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24